



HF4 SERIES CARTRIDGE FILTER HOUSING



Industrial Filtration Housing Solutions

Accommodates 10 to 40 inch cartridges with various end caps.

Material: SUS 304, SUS316L.



Max. Design Working Pressure: 150 PSI.

Polished or Sandblast External Surface.

Multi-Round/Flat Top with hinge joint.

Housings are built according to China GB Standard.

Housing <7 elements come with hinge joint & handle.



Specifications

Model	A (mm)	B (mm)	C (mm)	D (mm)	F (mm)	H (mm)	In/Out	Drain
HF4-W5L2	250	500	1040	Ø200	145	260	1 ½" - 2"	½"
HF4-W5L3	250	600	1250	Ø200	150	340	1 ½" - 2"	½"
HF4-W5L4	250	700	1500	Ø200	150	340	1 ½" - 2"	½"
HF4-W7L3	300	700	1300	Ø250	150	390	1 ½" - 2"	½"
HF4-W7L4	300	800	1550	Ø250	150	390	1 ½" - 2"	½"
HF4-W11L3	360	700	1380	Ø300	200	440	2" - 3"	½"
HF4-W11L4	360	900	1620	Ø300	200	440	2" - 3"	¾"
HF4-W15L3	380	800	1420	Ø350	200	530	2" - 3"	¾"
HF4-W15L4	380	900	1660	Ø350	200	530	2" - 3"	¾"
HF4-W20L3	400	800	1460	Ø400	200	560	2" - 4"	¾"
HF4-W20L4	400	900	1700	Ø400	200	560	2" - 4"	¾"
HF4-W27L3	460	800	1530	Ø450	250	630	2" - 4"	¾"
HF4-W27L4	460	1000	1770	Ø450	250	630	2" - 4"	¾"



GFS INNOVATION (2006) PTE LTD
(Industrial Filtration Division)

No. 52, Ubi Ave 3, #05-36 Frontier, Singapore 408867

Tel: (65) 6846 4689 Fax: (65) 6846 4875

Email: enquiry@gfsfilter.com Website: www.gfsfilter.com

