

MBS SERIES MELT-BLOWN CARTRIDGES

Used as:

- a) Pre-Filter
- b) Final Filter



GFS MBS SERIES FILTERS

MBS filters are an all polypropylene depth filter cartridge produce by the latest melt- blown technology. By controlling microfiber diameter variations, it yields a graded pore media structure. Graded pore structure effect is to stop large particles on the outer portion of the cartridge while smaller particles become trapped as they process through the declining tortuous path in the cartridge.

APPLICATIONS

- Industrial
- Chemical process
- Food/beverages
- Water


ADVANTAGES

- Fiber migration free surface treatment
- High integrated strength, no support core required
- High flowrate, low pressure drop
- Large contaminant retention, extended service life
- Broad chemical compatibility
- Economically priced


The Section of PP filter cartridge

Coarse outer layer provides enough dirty- absorbent space, reduces filter resistance and provides enough structure rigidity.


Fine inner layer intercepts small particles assuring the filter precision.







The Filter Efficiency Diagram



The Pressure Loss Diagram



End Cap Configuration



Ordering Information

| Cartridge Model | Length | - | Micron Rating | End cap style | Gasket/ O-Ring Material |
|--|---|---|--|--|---|
| MBS | 4.8=5" (125mm) 10=10" (250mm) 20=20" (508mm) 30=30" (762mm) 40=40" (1016mm) | | 0.5,1, 5,10, 25, 50 & 100 BB – Big Diameter (4.5"O/D) | DOE = No symbol 222 O-Ring/Flat = 3 222 O-Ring/Spear = 8 226 O-Ring/Spear = 7 | Buna N = B Silicone = S Viton = V |
| Example: MBS10-005, 5 micron, 10" length | | | | | |



Ultimate in Filtration

GFS FILTRATION PTE LTD
No.52, Ubi Ave 3, #05-36 Frontier, Singapore 408867
Tel: (65) 6846 4689 Fax: (65) 6846 4875
Email: enquiry@gfsfilter.com Website: www.gfsfilter.com

GFS FILTRATION (M) SDN BHD
No.31, Jalan Tabla 33/21, Shah Alam Technology Park
40400 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: 603-5122 2988 Fax: 603-5122 5388
Email: sales@gfsfilter.com Website: www.gfsfilter.com