

PENTEK MICROGUARD SERIES MEMBRANE FILTER CARTRIDGE

IDEAL FOR POINT-OF-USE APPLICATIONS



Pentair Pentek® MicroGuard Series membrane filters provide safer and cleaner drinking water without incorporating chemicals into the media or adding chemicals to the filtered water.

The MG-10MCB is uniquely designed with integral carbon block and sediment pre-filtration for the reduction of chlorine taste & odor and for providing extended life of the internal membrane element. This cartridge has 2.5 times greater filtration surface area than some anti-microbial carbon blocks, and operates at a higher flow rate with lower pressure drop. This makes the MG-10MCB ideal for Point-of-Use (POU) applications.

FEATURES/BENEFITS

Reduces particles as small as 0.15 micron in size by mechanical means

Membrane filtration provides 99.9999% reduction of bacteria and 99.9999% reduction of virus by mechanical means*

Combined carbon block and sediment pre-filtration for extended life and chlorine taste & odor reduction

Utilizes highly asymmetric polyethersulfone membrane with proprietary hydrophilic formulation for immediate wetting and high flow

Double O-ring endcap seals for absolute sealing in Pentair Pentek 3G housings

No electrical power required

Retains natural mineral content of water

SPECIFICATIONS

Filter Media – Polyethersulfone

Endcaps – Top: Polystyrene
Bottom: Polypropylene

Membrane Assembly – Polystyrene, epoxy resin

Carbon Pre-filter - Activated carbon, synthetic polymeric fibers & binders

Netting – Polyethylene

O-ring Seals – EPDM

Temperature Rating – 40-140°F (4.4-60°C)

*Based on manufacturer's internal testing.
EPA EST. NO. 086074-NH-001

RECOMMENDED OPERATING CONDITIONS

MODEL #	PART #	PRESSURE DIFFERENTIAL	STORAGE TEMPERATURE RANGE	pH RANGE	OPERATING PRESSURE RANGE	WATER TURBIDITY
MG-10MCB	255420-43	88 psi (6.1 bar) max	35-104° F (2.0-40° C)	2-12	5-88 psi (0.35-6.1 bar) max	<1 NTU

SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (ABSOLUTE)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*	ESTIMATED CAPACITIES**
MG-10MCB	255420-43	2.88" x 10.28" (73 mm x 261 mm)	0.15	11 psi @ 1 gpm (0.76 bar @ 3.8 Lpm)	200-600 gallons (757-2,271 L)

*Based on manufacturer's internal testing.

**Capacities may vary depending on local water quality, type of pre-filtration and acceptable minimum flow rate.

Not certified for sale in California, Iowa, or Wisconsin

NOTE: Cartridge not intended for converting wastewater or raw sewage into drinking water

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2016 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/en-US/aboutpentair/brands/. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

4003526 REV D JA16